

上海立诺防腐阀门制造有限公司

锻钢法兰端截止阀

### ■ 产品概述

产品名称: 锻钢法兰端截止阀(螺栓式阀盖)150LB~2500LB

产品类别: 锻钢截止阀

锻钢截止阀标准材质明细表



## 技术参数和性能

序号	零件名称	CS to ASTM	AS to ASTM	SS to ASTM	
		Type A105	Type F22	Type F304(L)	Type F316(L)
1	阀体	A105	A182 F22	A182 F304(L)	A182 F316(L)
2	垫片	Corrugated SS+graphite		SS+PTFE	
3	螺栓	A193 B7	A193 B16	A193 B8	A193 B8M
4	圆柱销	A276 420		A276 304	
5	填料压套	A276 410		A182 F304(L)	A182 F316(L)
6	活节螺栓	A193 B7	A193 B16	A193 B8	A193 B8M
7	螺母	A194 2H	A194 4	A194 8	A194 8M
8	阀杆螺母	A276 410			
9	螺母	A194 2H	A194 4	A194 8	A194 8M
10	铭牌	SS			
11	手轮	A197			
12	填料压板	A216 WCB		A351 CF8	
13	填料	Flexible Graphite		PTFE	
14	阀盖	A105	A276 304	A182 F304(L)	A182 F316(L)
15	阀杆	A182 F6	A182 F304	A182 F304(L)	A182 F316(L)
16	阀瓣	A276 420	A276 304	A276 304(L)	A276 316(L)
适用介质		水、蒸汽、油品等		水、蒸汽、油品等	硝酸、醋酸等
适用温度		-29℃~425℃		-29℃~550℃	-29℃~180℃

### ■ 主要连接尺寸

NPS		1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	
L(RF) L1(BW)	150LB	108	117	127	140	165	203	
	300LB	152	178	203	216	229	267	
	600LB	165	190	216	229	241	292	
H(开)	150LB~300LB	166	171	207	240	258	330	
	600LB	171	207	240	258	330	380	
W		100	100	125	160	160	180	
重量	150LB	RF	4.5	6.9	9.8	13.5	19.5	28.0
		BW	2.3	3.6	7.8	8.2	12.0	15.0
	300LB	RF	4.8	7.7	11.0	16.8	21.2	32.6
		BW	2.8	4.0	8.5	9.2	12.6	16.8
	600LB	RF	5.6	7.8	12.5	17.0	23.5	38.8
		BW	3.4	4.7	9.2	10.5	13.3	18.9